

## SAFETY DATA SHEET

# **SECTION 1: Identification of the substance / mixture and of the company / undertaking**

**1.1** Product Identifiers Product Name: AW 406 SDS Number: AW 406-2015 Product Type: Solvent

**1.2** Relevant identified uses of the substance or mixture and uses advised against.

Product Use: Solvent

**1.3** Detail of the supplier of the safety data sheet

Manufacture / Supplier / Importer: Tabriz Oil Refining Company

> 5 Tabriz – Azarshar Road Tabriz, East Azerbaijan, IR.Iran. Postal Cod: 5197131111 www.tabrizrefinery.co.ir

> > \_\_\_\_\_

**Contact person:** General Information +98-4121148305 info@tbzrefinery.co.ir

**Emergency telephone number:** +98-4121149117-118



# SECTION 2: Hazard Identification

2.1) Classification of the substance or mixture

H225: Highly flammable liquid and vapor Cat: 2 H304: May be fatal if swallowed and enters air ways Cat: 1 R67: Vapor may cause drowsiness and dizziness R38: Irritating to skin R11: Highly flammable R65: Harmful, may cause lung damage if swallowed

2.2) Label Elements

Hazard Pictogram



GHS02



GHS07



GHS08



Signal word: Danger

Hazard statement: Highly flammable liquid and vapor may be fatal if swallowed and enters airways.

Precautionary statement:

- Wear protective gloves / protective clothing / eye protection /

face protection

- Dispose of contents and container in accordance with local,

regional, national and international regulations

- Store in a well -ventilated place, keep cool
- Keep away from heat / sparks / open flames / hot surfaces
- No Smoking
- Keep container tightly closed
- Use only outdoor or in a well-ventilated area
- Avoid release to the environment
- Ground / bond container and receiving equipment
- Use explosion proof electrical equipment
- Use only non-sparking tools
- Remove / take off immediately all contaminated clothing,

rinse skin with water / shower

- Remove victim to fresh air and keep at rest in a position

comfortable for breathing collect spillage

- Take precautionary measures against static discharge
- Avoid breathing vapor / spray

## **SECTION 3: Composition / information on ingredients**

Substance / mixture: Mixture



Substance Name	% by weight	classification
Hydrocarbon	100%	R10, R65, R66, R67, R20
(IBP : 62 -		H226, H336, H304
FBP:82°C)		
See section 9		

# SECTION 4: First aid measures

### **4.1**) Description of first aid measures

Inhalation:	Provide fresh air
	Keep at rest
	In case of shortness of breath, give oxygen
	when in doubt or if symptoms are observed, get
	medical advice .

Skin contact: Take off immediately all contaminated clothing.

After contact with skin, wash with plenty of water and when in doubt or if symptoms are observed, get medical advice.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least is 15 minutes

In care of ingestion: Call a physician immediately. Do not induce vomiting.

Rinse mouth.

\_\_\_\_\_



Protection of first aid personnel:Pay attention to self-protection.When in doubt or if symptoms are observed, get medical advice.Treat symptomaticallyNever give anything by mouth to an unconscious person or a person with cramps

# **4.2**) Most important symptoms and effects, both acute and delayed

Inhalation: Vapors may cause drowsiness and dizziness, may cause respiratory irritation. Inhalation of high vapor concentration can cause CNS- depression and narcosis, headache, dizziness, tiredness, nausea and vomiting

Skin contact: Repeated exposure may cause skin dynes or cracking, erythema (redness)

Eye Contact: May cause eye irritation. Repeated or prolong exposure cause redness.

Ingestion: Aspiration hazard if swallowed – can enter lungs and cause damage. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.

\_\_\_\_\_



**4.3**) Indication of any immediate medical attention

and special treatment needed

No data available

# **SECTION 5:** Fire fighting measures

# 5.1) Extinguishing Media

Suitable: Water spray, foam, carbon dioxide, dry chemical extinguishing media which must not be used for safety reasons: Strong water jet.

**5.2**) Special hazard arising from the substance or mixture

Fire hazard: Flammable

Specific hazard: The pressure in sealed containers can increase under the influence of heat. Heating causes rise in pressure with risk of bursting. Vapors can form explosive mixtures with air, are heavier than air and may spread along floors, can travel considerable distance to an ignition source where they can ignite, flash back or explode.

Do not allow turn off from fire fighting to enter drains or water courses.

# 5.3) Advice for fire fighting

Evaluate area, special protective equipment for fire fighters. In case of fire wear SCBA apparatus. Use water spray to protect personnel and to cool endangered containers. Collect



contaminated fire extinguishing water separately. This must not be discharged into drains.

### SECTION 6: Accidental release measures

# **6.1**) Personal precautions, protective equipment and emergency procedures.

For non-emergency personnel: Evacuate area, use personal protective equipment. Provide adequate ventilation. Stay upwind/keep distance from source. Avoid contact with skin and eyes. Do not breathe vapor/spray. Keep away from heat, hot surfaces, sparks open flames and others ignition sources. No smoking .Ensure that all equipments are adequately grounded. Get medical / attention, if you feel unwell.

For emergency responders: Ensure producers and training for emergency decontamination and disposal are in place.

#### 6.2) Environmental Precautions

Do not allow to enter into surface water or drains. Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic release.



**6.3**) Methods and material for containment and cleaning up.

Remove all sources of ignition. Do not smoke. Provide adequate ventilation.

Clean up methods: -Small spillage: Stop leak if safe to do so. Remove all sources of ignition. Do not smoke. Provide adequate ventilation.

Clean up methods: -Small spillage: Stop leak if safe to do so.

- Absorb with liquid binding material (e.g. sand, earth)
- -Large spillage: Stay up wind / keep distance from source. Collect in closed and suitable containers for disposal. Delivery to an approved waste disposal company. Material can create sloppy conditions.

**6.4**) Reference to other sections:

See section 13 for disposal

See section 8 for personal protective equipments

#### SECTION 7: Handling and storage

#### 7.1) Precaution for safe handling

#### Handling:

- Provide adequate information, instruction and training for operators.

- Provide adequate ventilation.

- Use personal protective as required.

Version 1.0: Date of issue / Date of revision: November 2014



- Avoid contact with skin, eyes and clothes.
- Do not breathe vapor / spray.
- Take precautionary measures against static discharges.
- -Ensure that the equipment is adequately grounded.
- Keep away from heat, hot surface, sparks, open flames and other ignition sources.
- No smoking

-Take any precaution to avoid mixing with incompatible materials.

- Do not allow to enter into surface water or drains.

- Advices on general occupational hygiene: Keep good industrial hygiene. Wash hands and face before breaks and immediately after handling of the product. Take off contaminated clothing. Keep away from food, drink and animal feeding stuffs.

# **7.2**) Conditions for safe storage, including any incompatibilities

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place.

Keep / store only in original container. Keep in a bonded area. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not store near or with any of the incompatible materials.

Packaging materials: Stainless steel, carbon steel NOTE: In case of using non-metallic (non- conductive) container such as PE, manufacture's advice taking is essential.



**7.3**) Specific and use (s):

Recommendations: not available

Industrial sector specific solution: not available

# SECTION 8: Exposure Control /Personal protection

# 8.1) Control Parameters

Exposure limit value: See bellow tables Recommended monitoring procedures: Concentration measurement in air EN 689.

Workers	
1) Acute – systematic effect, inhalation	Not Available
2) Long term - systematic effect dermal	Not Available
3) Long term - systematic effect , inhalation	Not Available
General Population	
1) Acute – systematic effect, inhalation	Not Available
2) Long term - systematic effect oral	Not Available
3) Long term - systematic effect , inhalation	Not Available

PNEC (Additional Information): No data available

\_\_\_\_\_



11 of 17

# 8.2) Exposure Controls

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (EN 140) Full –face mask (EN 136) Filter –type A2 (EN 141) SCBA (EN 137)

Hand Protection: Protective gloves (EN 374, EN 420) Breakthrough time (maximum wearing time) > 240 –class 5 .The section of specific gloves for a specific application and time of use in a working area , should also take into account other factors on the working space , such as physical requirements (protection against cutting) , nitril rubber.

Eye protection: Safety glasses with side shield goggles (EN 166)

Body protection: Wear chemical resistant apron (nitril rubber)

Thermal hazard protection: Not required under normal use.

Engineering control measures: -Provide adequate ventilation

Version 1.0: Date of issue / Date of revision: November 2014

\_\_\_\_\_





- Use only in area provided with appropriate exhaust ventilation.

- A washing facility / water for eye and skin cleaning purpose should be present.

- Take precautionary measures against static discharge.

- Provide adequate precautions such as electrical grounding and bonding or inert atmosphere.

Organizational measures to prevent / limit releases, dispersion and exposure.

Environmental exposure control : Do not enter into surface water or drains. Comply with applicable community environmental protection legislation.

# **SECTION 9: Physical and Chemical Properties**

**9.1**) Information on basic physical and chemical properties

Appearance:LiquidColor :Min. 25 (Saybolt)Odor:Merchantable



Odor threshold: Not available				
PH: Not available Melting point / Freezing point: Initial boiling point (IBP): Boiling range:	Not available Min 62 °C 62-82 °C			
Distillation: 50% (@ 63-71 °C), 90% (@ 64-74 °C)				
Dry point: 80-98 °C				
Total sulfur: 0.05 wt. % (maximum)				
Aromatic content: 7 vol. % (maximum)				
Flash point:	Not available			
Evaporation rate:	Not available			
Upper / lower flammability limit:	Not available			
Vapor pressure:	Not available			
Vapor density:	Not available			
Relative density:	Not available			
Solubility in water:	Not available			
Partition coefficient:	Not available			
Auto – ignition temperature:	Not available			
Decomposition temperature:	Not available			
Viscosity:	Not available			
Explosive properties:	Not available			
Oxidizing properties:	Not available			
Solubility (ies):	Not available			
Explosive limit:	Not available			

# 9.2) other information: No additional information

\_\_\_\_\_

-----



### SECTION 10: Stability and Reactivity

10.1) Reactivity Flammable liquid – stable

10.2) Chemical stability The product is stable under storage at normal ambient temperature / pressure.

10.3) Possibility of hazardous reactions Vapors can form explosive with air

10.4) Conditions to avoid Keep away from sources of ignition (e.g. sparks, open flame).

10.5) incompatible materials Oxidizing agents

10.6) Hazardous decomposition products No specific data

# **SECTION 11: Toxicological Information**

11.1) Information on toxicological effects: Not available



## **SECTION 12: Ecological Information**

12.1) Toxicity: Not available

12.2) Persistence and degradability:	Not available		
12.3) Bioaccumulative potential:	Not available		
12.4) Mobility in soil:	Not available		
12.5) Results of PBT and vPvB assessment: Not			

available

#### SECTION 13: **Disposal Considerations**

13.1) Waste treatment methods: In accordance with local and national regulations. Handle with care. Dispose according to legislation. Collect and dispose of waste product an authorized disposal facility.

#### SECTION 14: **Transport Information**

14.1) UN umber:

Mixture

- 14.2) UN proper shipping name: AW406
- 14.3) Transport hazard class (es)



14.3.1) Overland transport
Class: 3 – flammable liquid Packing Group: III
Hazard identification number (kemler No.): Not Available
Classification code: Not Available
ADR / RID Labels : 3-flammable liquid



14.3.2) In land waterway transport (ADN)

Not Available

14.3.3) Transport by sea

Not Available

14.3.4) Air transport

Not Available

14.5) Environmental hazard

Not Available

14.6) Specific precautions user: Not Available

14.7) Transport in bulk according to Annex II of MARPOL

73/78

Not Available



### SECTION 15: Regulatory Information

15.1) Safety, breath, environmental regulations / legislation specific for the substance or mixture Not Available

15.2) Chemical safety assessment Not Available

# SECTION 16: Other Information

R10: Flammable

- R65: Harmful may cause lung damage
- R66: Repeated exposure may cause skin dryness or

#### cracking

- R67: Vapor may cause drowsiness or dizziness
- R48: Danger of serious damage to health by prolonged

#### exposure

- H226: Flammable vapor / liquid
- H304: May fatal if swallowed and enters air way
- H336: May cause drowsiness or dizziness
- H327: Cause damage to organs through prolongs or

repeated

Version 1.0: Date of issue / Date of revision: November 2014